

Earth-Rite® OMEGA II



The **Earth-Rite® OMEGA II** is a compact panel mounted static grounding module that can monitor a range of resistance values, based on the grounding application and installation requirements of specific processes.

Inquiry > Click here to submit a product related query or a request for quotation.

The Earth-Rite OMEGA II monitors the resistance of the static grounding circuit for processes where a risk of static charge accumulation on the equipment could result in an incendive electrostatic spark within locations that have potentially flammable atmospheres present.

It is specified primarily for applications where an alternative means of ground status indication is provided, e.g. via panel mounted indicators or remote indicator stations, as opposed to more regular grounding solutions in the **Earth-Rite®** range.

The DIN rail mountable module can be located in an electrical panel mounted in a non-hazardous area or inside an XP certified enclosure located inside the hazardous area.

Two dry contacts can be used to switch power to additional ground status indicators or interlock with the process to shutdown product transfer when the Earth-Rite OMEGA II detects an open circuit on the path to ground.



Earth-Rite OMEGA II

Ground Resistance Monitoring Set Points


The Earth-Rite OMEGA II is designed specifically for monitoring the static grounding of process equipment and has 4 resistance set points depending on the installation and operating characteristics of the application. It can also be installed to monitor the resistance of bonding circuits and lightning protection grounding points.

- > 0 ohms to 2 ohms to monitor low resistance bonding paths.
- > 0 ohms to 4 ohms.
- > 0 ohms to 10 ohms (recommended values of resistance in IEC 60079-32 & NFPA 77).
- > 0 ohms to 600 ohms (to monitor the grounding of rotating machinery).

Earth-Rite® OMEGA II

Technical Specification

Power supply:	24V dc stabilised supply (Supply voltage range: 18V to 30V dc). Up to four OMEGA II modules can be powered by Newson Gale's 24V DC power supply (Product code: VESF80)
Power rating:	5 Watts
Power supply protection:	500 mA fast blow fuse connected into the supply circuit (not included).
Ambient temperature range:	-40°C to +60°C -40°F to + 140°F.
Ingress Protection:	Type 1
Module nett weight:	0.55 lbs (0.25 kg)
Enclosure material:	Polycarbonate
Output Contact relay rating:	1 pair of NO/NC changeover contacts 250 V AC, 5 A, 500 VA max resistive. 30 V DC, 2 A, 60 W max resistive. The relay is designed to switch Low Voltage circuits or Extra Low Voltage circuits. A slave relay should be used for switching Low Voltage circuits and Extra Low Voltage circuits at the same time.
Resistance monitoring set points:	0 ohms to 2 ohms. 0 ohms to 4 ohms. 0 ohms to 10 ohms (IEC 60079-32 & NFPA 77 recommended). 0 ohms to 600 ohms (typically used for grounding rotating equipment).
Mechanical dimensions:	Units in inches: 3.5 x 4.1 x 2.3



Hazardous Area Certification

Europe / International:	North America:
IECEX [Ex ia Ga] IIC (gas & vapour) [Ex ia Da] IIIC (combustible dusts) Ta = -40°C to +60°C IECEX EXV 19.0066X IECEX certifying body: ExVeritas	NEC 500 / CEC (Class & Division) Intrinsically safe associated apparatus for supply to locations classified: Class I, Div. 1, Groups A, B, C, D Class II, Div. 1, Groups E, F, G Class III, Div. 1 Ta = -40°C to +60°C Ta = -40°F to +140°F OSHA recognised NRTL: CSA
ATEX Ⓜ II (1)GD [Ex ia Ga] IIC (gas & vapour) [Ex ia Da] IIIC (combustible dusts) Ta = -40°C to +60°C ExVeritas 19ATEX0561X ATEX Notified Body: ExVeritas	NEC 505 & 506 (Class & Zoning) Class I, Zone 0, [AEx ia], IIC (gas & vapour) Class II, Zone 20, [AEx iaD], IIIC (combustible dusts)
	CEC Section 18 (Class & Zoning) [Ex ia] IIC

Additional Certification

Safety Integrity Level:	SIL 2 (in accordance with IEC/EN 61508).
SIL assessment body:	ExVeritas.
EMC Tested:	to EN 61000-6-1, EN 61000-6-3, FCC Part 15 (Class B Digital).



The Earth-Rite® OMEGA II forms part of the Earth-Rite® range of Static Grounding and Bonding Equipment available from Newson Gale Ltd.

Earth-Rite® OMEGA II

System Options

Newson Gale supplies a range of product options that enhance the control and general safety of transfer processes and aid engineers with system installations and routine system service checks. Contact Newson Gale or your local Newson Gale representative for more information on the range of options available.

Universal Resistance Tester

The URT is designed to provide owners of Newson Gale **Earth-Rite®** and **Bond-Rite®** static grounding systems with a means of regularly testing the grounding settings for their system on a routine basis.

Periodic testing with the URT verifies that the grounding system's **GO/NO GO** settings are working in compliance with the recommendations of:

NFPA 77: "Recommended Practice on Static Electricity."

IEC 60079-32-1: "Explosive atmospheres. Part 32-1: Electrostatic hazards, guidance."

The easy to use tester consists of a pair of switches that enable an electrician to set up the resistance level at which the grounding system should be working and conduct a **PASS / FAIL** test at the required setting.

Earth-Rite® and **Bond-Rite®** products that can be tested with the URT:

- > Earth-Rite® II PLUS
- > Earth-Rite® II FIBC (both 10 meg-ohm and 100 meg-ohm variants)
- > Bond-Rite® CLAMP
- > Bond-Rite® EZ
- > Bond-Rite® REMOTE
- > OhmGuard® (both 10 ohm and 100 ohm variants)



Earth-Rite® OMEGA II

Contact Us > Your inquiry will be processed rapidly via our webform enquiry service. If you would prefer to call us, or e-mail us, please use the contact details provided below.

System Options

Hazardous Area Strobe Light

The strobe light is mounted in an elevated position and when the equipment is correctly grounded, flashes continuously informing personnel that a transfer process is underway and is protected from the static hazard. The strobe light can be used in conjunction with the **Earth-Rite RTR** and **Earth-Rite PLUS**.

- > 115 V / 230 V AC and 24 V / 48 V DC options
- > Amber, Green & Red strobe colour options



2-Pole Surface Mountable connector

With this assembly operators tasked with earthing mobile process equipment will have a dedicated earthing point to attach the easy to use screw thread connector. The 'plug and play' connector can interface with all Newson Gale 2 core systems to provide earth monitoring capability on a wide range of mobile processes and equipment where generic earthing clamps cannot be used.

The conical shape design prevents powder deposit build up over time and aids in clean down operations.

- > Made using Stainless Steel 304 with Viton O-Rings
- > IP 66
- > -40°C to 60°C
- > Various lengths of straight or spiral Hytrel cable available



United Kingdom
Newson Gale Ltd
Omega House
Private Road 8
Colwick, Nottingham
NG4 2JX, UK
+44 (0)115 940 7500
groundit@newson-gale.co.uk

Deutschland
IEP Technologies GmbH
Kaiserswerther Str. 85C
40878 Ratingen
Germany
+49 (0)2102 5889 0
erdung@newson-gale.de

United States
IEP Technologies LLC
417-1 South Street
Marlborough, MA 01752
USA
+1 732 961 7610
groundit@newson-gale.com

South East Asia
ngsea@newson-gale.com