

## VESX45/PGS Personnel Grounding Strap



The **VESX45/PGS** is a heavy duty stainless steel grounding clamp and wrist strap assembly that provides operators working in hazardous areas with an additional layer of protection against fires or explosions caused by static electricity.

**Inquiry** > Click here to submit a product related query or a request for quotation.

Through their own movement people can generate large amounts of static charge if they are not grounded. In some cases, as much as 30,000 volts can be carried by people who are completely unaware that they themselves are the potential source for an electrostatic spark discharge that could ignite a flammable atmosphere.

If the operating requirements of certain processes cause the loss of direct contact between the operator's static dissipative safety shoes and the static dissipative flooring of the plant, the VESX45/PGS provides an added layer of protection to ensure the operator is grounded via the plant or bonded to the equipment they are interacting with.

For example, an operator may need to stand on a ladder to tip powder into a large mixer and in the process of moving to the ladder loses contact with the static dissipative flooring.

To ensure static cannot accumulate on the operator, by fastening the grounding strap to their wrist, any charge generated by their movement can be dissipated to ground by

direct contact to a verified ground connection.

*\*refer to page 2 of this datasheet to see what IEC 60079-32-1 and NFPA 77 recommend with respect to the use of personnel grounding straps.*

### Product Features

**FM & ATEX approved Heavy Duty stainless steel grounding clamp** with tungsten carbide teeth mounted in a side-by-side configuration to provide a high degree of clamp stability and to bite through rust, coatings and deposits of process material.

**12 ft. (3.7 m) spiral cable** fitted with a quick release connector enables operators to detach themselves in the event that they need to vacate the process area immediately.

**1 meg-ohm safety resistor** mounted in the cable to prevent stray electrical currents passing through the operator.

**Adjustable anti-allergy** wrist strap to fit a wide range of wrist sizes.



**Stainless Steel VESX45/PGS personnel grounding strap**



**Adjustable wrist strap with quick release connector**

## VESX45/PGS Personnel Grounding Strap

### Technical Specification

VESX45/PGS	
<b>Clamp details:</b>	FM/ATEX approved Heavy Duty static grounding clamp.
<b>Clamp material:</b>	Stainless handles (SS 304) and spring (SS 302). Tungsten carbide teeth for maximum penetration.
<b>Clamp dimensions:</b>	4.7" x 1.0" (120 mm x 25 mm) (length x width).
<b>Clamp jaw opening:</b>	0.6" (15 mm) maximum.
<b>Wrist strap:</b>	Anti-allergy adjustable strap.
<b>Electrical safety resistor:</b>	1 meg-ohm resistor mounted in the conductor.
<b>Cable details:</b>	12 ft. (3.7 m) single pole spiral conductor fitted to a quick release connector.

**Contact Us >** Your inquiry will be processed rapidly via our webform enquiry service. If you would prefer to call us, or e-mail us, please use the contact details provided below.

\* Both section 11.4 of IEC 60079-32-1 and section 8.2.3.3 of NPFA 77 state the following:

“The simplest type of commercial device is an earthing bracelet with a built-in resistor typically giving a resistance to ground of about 100 kΩ for shock protection. Wrist straps of this type have the greatest utility at ventilation hoods and at other locations where limitation on the operator’s mobility can be tolerated. Breakaway wrist tether systems could be necessary where emergency egress is needed. A hood can be equipped with two external coiled earthing cords with cuff attachments that can be removed and kept by individual users.”

**IEC 60097-32-1: Explosive atmospheres, Electrostatic Hazards, Guidance.**

**NFPA77 “Recommended Practice on Static Electricity”.**

### Hazardous Area Certification

#### Grounding Clamp

##### Europe / International:

<b>ATEX</b> II 1 GD T6 ATEX Notified Body: SIRA.	<b>FM approved to FM Standard 6085:</b> Approval Body: FM Global.
--	--

**United Kingdom**  
 Newson Gale Ltd  
 Omega House  
 Private Road 8  
 Colwick, Nottingham  
 NG4 2JX, UK  
 +44 (0)115 940 7500  
 groundit@newson-gale.co.uk

**Deutschland**  
 IEP Technologies GmbH  
 Kaiserswerther Str. 85C  
 40878 Ratingen  
 Germany  
 +49 (0)2102 5889 0  
 erdung@newson-gale.de

**United States**  
 IEP Technologies LLC  
 417-1 South Street  
 Marlborough, MA 01752  
 USA  
 +1 732 961 7610  
 groundit@newson-gale.com

**South East Asia**  
 ngsea@newson-gale.com