

## 1 EU - Type Examination Certificate

2 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

3 Certificate Number: ExVeritas 19ATEX0547X Issue: 1

4 Equipment: Bond-Rite REMOTE

5 Manufacturer: Newson Gale Limited

6 Address: Omega House, Private Road 8, Colwick, Nottingham, NG4 2JX, United Kingdom

7 This equipment and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

8 ExVeritas, Notified Body number 2804 in accordance with Article 17 of the Council Directive 2014/34/EU of 26 February 2014, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to design and construction of equipment and protective systems for use in potentially explosive atmospheres given in Annex II to the Directive

9 Compliance with the applicable Essential Health and Safety Requirements has been assured by compliance with the following Standards and section 16 of this certificate:

EN IEC 60079-0: 2018


EN 60079-11:2012

EN 60079-31:2014

10 If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

11 This EU-Type Examination Certificate relates only to the design, construction, examination and tests of the specified equipment or protective system in accordance to the Directive 2014/34/EU. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.

12 The marking of the equipment shall include the following:

 II 1 GD Ex ia IIC T4 Ga  
Ex ta IIIC T135°C Da  
(Ta = -40°C to +60°C)

On behalf of ExVeritas



Peter Lauritzen  
Managing Director



This certificate may only be reproduced in its entirety and without any change, schedule included.

The status of this certificate can be verified at [www.exveritas.com](http://www.exveritas.com)  
For help or assistance relating to this certificate, contact [info@exveritas.com](mailto:info@exveritas.com).  
ExVeritas ApS, Severinsmindevej 6, 4420 Regstrup, Denmark.  
ExVeritas® is a registered trademark, unauthorised use will lead to prosecution.

### 13 Description of Equipment or Protective System

The Bond-Rite REMOTE provides an intrinsically safe output to a clamp, which is connected to the equipment via a bonding cable. The equipment is designed to be used with all types of metallic plant such as drums, road and rail tankers, IBCs, mixing vessels and other similar applications. Connection of the clamp prevents a dangerous build up of static charge during transfer, handling or mixing operations, enabling it to 'bleed' safely to earth. Its use assumes that no charge is present prior to the clamp being attached. The Bond-Rite REMOTE provides an indication that the resistance between clamp and the plant to which it is attached is less than 10 ohms. Under these circumstances, an LED on the cover will be illuminated. A loop connection to earth also ensures that the item of plant is connected to earth.

The Bond-Rite REMOTE has two power options: it is either powered by an internal battery or is supplied from an external Newson Gale power supply unit (ER UPS).

The safety description of the Bond-Rite REMOTE is as follows:

|   |                           |
|---|---------------------------|
| Power supply input (for units without the battery fitted) | Output to clamp and earth |
| U <sub>i</sub> = 9.0 Vdc                                  | U <sub>o</sub> = 11.1 V   |
| C <sub>i</sub> = 0  | I <sub>o</sub> = 0.143 A  |
| L <sub>i</sub> = 0  | P <sub>o</sub> = 0.26 W   |
|   | C <sub>o</sub> = 0.9 µF   |
|   | L <sub>o</sub> = 1734 µH  |

#### 13.1 Details of Change

The following changes are introduced in issue 1<sup>\*1</sup> of the certificate:

- Transfer of the certificate from ExVeritas UK, Notified Body number 2585 to ExVeritas Denmark, Notified Body number 2804. Certificate number remains unchanged.

### 14 Descriptive Documents

#### 14.1 Associated Report and Certificate History:

| Report Number | Cert Issue Date | Issue | Comment   |
|---------------|-----------------|-------|---|
| R2249/A/5     | 18/11/2019      | 0     | Initial issue of the Prime Certificate          |
| EXV3140A      | 12/01/2021      | 1     | Issue of the first variation, see section 13.1. |

#### 14.2 Compliance Drawings:

##### Issue 0

| Title:  | Drawing No.:      | Rev. Level: | Date:      |
|---|-------------------|-------------|------------|
| Bond-Rite II  | AA0204R1A-CERT    | A           | 07/02/2011 |
| Bond-Rite II Certified Parts List                       | AA0204R1A-PLC     | A           | 07/02/2011 |
| Bond-Rite II Board PCB Layout                           | AA0204R1A-CB-CERT | A           | 07/02/2011 |
| Bond-Rite II Board PCB Layout                           | AA0204R1A-CT-CERT | A           | 07/02/2011 |
| Bond-Rite II Board PCB Layout                           | AA0204R1A-SS-CERT | A           | 07/02/2011 |
| Bond-Rite Remote Using GRP or Stainless Steel Enclosure | B-RR-2011 GA      | 2A          | 11/07/2012 |
| Certification Detail Bond-Rite Remote                   | BRR LAB 1         | AG          | 21/10/2019 |

Certificate: ExVeritas 19ATEX0547X

Issue 1

This certificate may only be reproduced in its entirety and without any change, schedule included.

For help or assistance relating to this certificate, contact [info@exveritas.com](mailto:info@exveritas.com).

ExVeritas ApS, Severinsmindevej 6, 4420 Regstrup, Denmark.

ExVeritas® is a registered trademark, unauthorised use will lead to prosecution.

## 15 Conditions of Certification

### 15.1 Special Conditions for Safe Use

1. The replacement battery shall be one of the following types only:
  - Ultralife type U9VL-J
  - Varta type 6122

These batteries are intrinsically safe and may be replaced when the equipment is in a hazardous area. The battery must be removed when the equipment is externally powered.

2. The number of Bond-Rite REMOTE units that can be connected to the power supply with an output voltage ( $U_o$ ) not exceeding 9.0 V depends on the following:
  - External capacitance of the power supply,  $C_o(P/S)$
  - External inductance of the power supply,  $L_o(P/S)$
  - Total capacitance of all the cables between the power supply and the connected Bond-Rite REMOTE units,  $C_{cable}$
  - Total inductance of all the cables between the power supply and the connected Bond-Rite REMOTE units,  $L_{cable}$
  - In the system comprising a single power supply and multiple Bond-Rite REMOTE units,  $C_{cable}$  must not exceed  $C_o(P/S)$  and  $L_{cable}$  must not exceed  $L_o(P/S)$

### 15.2 Conditions for Use (Routine tests)

The Manufacturer shall comply with the following condition of manufacture:

1. The Bond-Rite REMOTE incorporates previously certified enclosures as listed below. It is therefore the responsibility of the manufacturer to continually monitor the status of the certification associated with these devices, and the manufacturer shall inform ExVeritas of any modifications of the devices that may impinge upon the explosion safety design of their products.

Certificate number

Details

IECEX PTB 08.0003U, PTB 01ATEX1061U ROSE Systemtechnik type 26. .... enclosure

IECEX PTB 07.0059U, PTB 01ATEX1101U ROSE Systemtechnik type 35. .... enclosure (s/s)

2. Each manufactured sample of the Bond-Rite REMOTE with a stainless steel enclosure shall be subjected to an electric strength test using a test voltage of 500 Vac applied between the circuit and enclosure for 60 s. Alternatively, a voltage of 20% higher may be applied for 1 s. There shall be no evidence of flashover or breakdown and the maximum current flowing shall not exceed 5 mA.

## 16 Essential Health and Safety Requirements

Essential Health and Safety Requirements are addressed by the standards listed in section 9 and where required the report listed in section 14.1

The manufacturer shall inform the Notified Body of any modifications to the design of the product described by this schedule.